THE PLUMBER'S THIRD HAND Garbage Disposal Installation Tool

Makes installing a Garbage Disposal as easy as 1-2-3!

Before installing Disposal, follow manufacturers instructions for installing the discharge elbow, electrical connection, dishwasher knockout (if applicable), and sink strainer.



- Place the garbage disposal directly beneath the sink strainer opening.
 Place the manufacturer's supplied parts on top of the garbage disposal in this order: snap ring, triangular flange with screws, base plate and fiber gasket.
- 2) Insert the installation tool through the sink strainer and into the opening of the garbage disposal. PUSH DOWN AND THEN PULL UP TO SECURE THE TOOLS BASE PLATE TO THE INSIDE WALL OF THE DISPOSAL.
- 3) Lift the disposal from the cabinet base about 2 inches. SPIN THE SPIN-DOWN CLOCKWISE DOWN INTO THE STRAINER OPENING. The weight of the disposal suspended from the tool will hold the sink strainer firmly in place. Two hands are now free to install the manufacturers supplied parts previously placed on top of the disposal to the strainer base. Tighten the TRIANGULAR PLATE screws firmly against the base plate.
- 4) Lift the disposal up to the sink strainer base. SPIN THE SPIN-DOWN INTO THE STRAINER OPENING. TURN THE SPIN-DOWN CLOCKWISE BRING-ING THE DISPOSAL FIRMLY AGAINST THE SINK STRAINER BASE. DO NOT OVER TIGHTEN. With two hands NOW FREE turn the manufacturers preinstalled locking ring counter clockwise securing the disposal to the lugs of the sink strainer base. Tighten it up.
- 5) TURN THE SPIN-DOWN COUNTER-CLOCKWISE UP APPROXIMATELY 6 INCHES and remove the installation tool.

If you have questions, contact us at 860-536-1860.

PATENT PENDING





Part number 3H2013